

Hartig

Precision external micrometer with 50 mm spindle travel, Measuring range: 100-150 mm



Order data

Order number	420900 100-150
GTIN	4250099609202
Item class	46P

Description

Version:

Stable spheroidal cast frame, hammer finish with hand temperature protection, friction clutch, and locking device. Precision lapped, carbide-tipped measuring faces. Accuracy better than DIN 863.

Advantage:

50 mm spindle travel, ideal for larger measurement ranges. Direct reading of the 1/100 mm on the large scale barrel.

Supplied with:

Without setting standard.

Packaging: sturdy box

Standard: Manufacturer's standard

Micrometer barrel graduations: 1/100 mm

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 4 μ m

Spindle \varnothing : 8 mm

Barrel \varnothing : 24 mm

Technical description

Barrel \varnothing	24 mm
Micrometer barrel graduations	1/100 mm
Scale divisions	0.01 mm

Spindle Ø	8 mm
Measuring range	100 - 150 mm
Calibration	B1
Error limit	4 µm
Standard	Manufacturer's standard
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Calibration External tube micrometer maximum measuring range 200 mm	012050 200
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 200 mm	022000 200

Accessories

Micrometer setting standard overall length 100 mm	421100 100
---	------------