

Hartig

## Precision external micrometer with 50 mm spindle travel, Measuring range: 200-250 mm



### Order data

Order number	420900 200-250
GTIN	4250099609226
Item class	46P

### Description

#### Version:

Stable spheroidal cast frame, hammer finish with hand temperature protection, friction clutch, and locking device. Precision lapped, carbide-tipped measuring faces. Accuracy better than DIN 863.

#### Advantage:

50 mm spindle travel, ideal for larger measurement ranges. Direct reading of the 1/100 mm on the large scale barrel.

#### Supplied with:

Without setting standard.

Packaging: sturdy box

Standard: Manufacturer's standard

Micrometer barrel graduations: 1/100 mm

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 5  $\mu$ m

Spindle  $\varnothing$ : 8 mm

Barrel  $\varnothing$ : 24 mm

### Technical description

Micrometer barrel graduations	1/100 mm
Spindle $\varnothing$	8 mm
Barrel $\varnothing$	24 mm

Measuring range	200 - 250 mm
Scale divisions	0.01 mm
Calibration	B1
Error limit	5 µm
Standard	Manufacturer's standard
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

### Services

Calibration External tube micrometer maximum measuring range 300 mm	012050 300
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 300 mm	022000 300