

Hartig

Large precision micrometer with rear anvil extension, Measuring range: 800-900 mm**Order data**

Order number	420920 800-900
GTIN	4250099610857
Item class	46P

Description**Version:**

Stable light metal cast frame, hammer finish with hand temperature protection, friction clutch, and locking device. Precision lapped, carbide-tipped measuring faces. Accuracy better than DIN 863. The screw-on rear anvil extension is lapped and carbide-tipped; it doubles the measuring range. Inner scale sleeve with scales for both measurement ranges.

Advantage:

Very large measuring range. After the rear anvil extension has been fitted, the micrometer is immediately ready for use. No additional setting block required. Direct reading of the 1/100 mm on the large scale barrel.

Supplied with:

Micrometer with 1 rear anvil extension. Without setting standard.

Note:

Versions up to 2000 mm measurement range available on request.

Special versions on request.

Packaging: sturdy box

Standard: Manufacturer's standard

Micrometer barrel graduations: 1/100 mm

Calibration: S3

Scale divisions: 0.01 mm

Error limit: 10 µm

Spindle Ø: 10 mm

Spindle travel: 50 mm

Barrel Ø: 24 mm

Weight: 5 kg

Technical description

Micrometer barrel graduations	1/100 mm
Scale divisions	0.01 mm
Spindle Ø	10 mm
Weight	5 kg
Spindle travel	50 mm
Measuring range	800 - 900 mm
Barrel Ø	24 mm
Calibration	S3
Error limit	10 µm
Standard	Manufacturer's standard
Measurement technology	analogue
Packaging	sturdy box
Type of product	External tube micrometer

Services

Calibration External micrometers with extensions Measuring range 800-900 mm	011210 800-900
Labelling laser-etched Type	018940
Calibration External micrometers with extensions Measuring range 800-900 mm	020450 800-900