

 Mahr

Digital external micrometer i-wi with interchangeable anvils, Measuring range: 0-25 mm



Order data

Order number	421323 0-25
GTIN	4059192063719
Item class	43A

Description

Version:

External micrometers **with non-rotating** spindle and **interchangeable anvils**. **Spindle pitch 5 mm per revolution** reduces the approach time. **10 mm tall characters** on high-contrast display. Practical HOLD function for freezing the measured value for reliable, error-free reading. Button for changeover between relative and absolute measurement. Zero setting in any position. A well-arranged tolerance display with additional warning limits allows the user to recognise whether the workpiece is within the tolerance limits.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Supplied with 1 battery No. 081560 size CR2032.

6 pairs of interchangeable anvils with:

- **Flat measuring faces Ø 6.5 mm.**
- **Disc anvils Ø 11.3 mm.**
- **Reduced measuring faces Ø 2 mm.**
- **Convex measuring faces Ø 7 mm.**
- **Blade anvils 0.75×7 mm.**
- **Cone 60° Ø 0.5 – 5.5 mm.**

Optional extras:

i-wi radio receiver No. 498912.

Packaging: sturdy box

IP Index of Protection: IP 65

Calibration: B1

Scale divisions: 0.001 mm

Scale divisions: 0.00005 inch

Error limit: 4 µm

Spindle Ø: 6.5 mm

Spindle pitch: 5 mm

Technical description

Spindle pitch	5 mm
Number of batteries contained	1
Scale divisions	0.001 mm
Spindle Ø	6.5 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Error limit	4 µm
Scale divisions	0.00005 inch
Measuring range	0 - 25 mm
Number of measuring tips	6
Calibration	B1
Digit height LCD display	10 mm
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	DIN 863
Reversible reading	mm / inch
Interface	MAHR i-wi radio system
Measurement technology	digital
Packaging	sturdy box
Type of product	micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100

Accessories

Radio receivers for Mahr i-wi Type STICK	498912 STICK
--	--------------