

Mitutoyo
Digital external micrometer, Measuring range: 0-25 mm

Order data

Order number	421500 0-25
GTIN	4946368673158
Item class	44A

Description
Version:

Digital external micrometer with compact design. Extra large LCD display (7.5 mm). Carbide-tipped anvils.

Supplied with:

1 battery No. 081560 size 357.

Packaging: sturdy box

Calibration: B1

Scale divisions: 0.001 mm

Error limit: 3 μ m

Spindle \varnothing : 6.35 mm

Spindle pitch: 0.5 mm

Technical description

Spindle pitch	0.5 mm
Spindle \varnothing	6.35 mm
Measuring range	0 - 25 mm
Error limit	3 μ m
Scale divisions	0.001 mm
Calibration	B1
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 357

Power supply	Battery-powered
Standard	DIN 863
Measurement technology	digital
Packaging	sturdy box
Type of product	micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 25 mm	022000 25
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100

Accessories

Button cell / special battery Battery type 357	081560 357
--	------------