

## Mitutoyo

### Digital external micrometer IP65 with data output, Measuring range: 125-150 mm



#### Order data

Order number	421525 125-150
GTIN	2050002041080
Item class	44A

#### Description

**Version:**

Error limits more accurate than the requirements of **DIN 863**.

Extra large LCD display (7.5 mm high) for quick, error-free reading, keyboard lock.

Carbide-tipped measuring faces.

**Shock-proof version.**

Measuring spindle hardened and ground.

**Function:**

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

**Supplied with:**

1 battery No. 081560 size 357, 1 setting standard from size 25 -50.

**Optional extras:**

No. 421525 and 421527. Data cable No. 497445.

Packaging: sturdy box

IP Index of Protection: IP 65

Calibration: B1

Calibration: B2

Scale divisions: 0.001 mm

Error limit: 3 µm

Spindle Ø: 6.35 mm

Spindle pitch: 0.5 mm

#### Technical description

Number of batteries contained	1
Scale divisions	0.001 mm
Calibration	B1
Calibration	B2
Error limit	3 µm
Measuring range	125 - 150 mm
Spindle pitch	0.5 mm
Article no of the battery / rechargeable battery fitted	081560 357
Spindle Ø	6.35 mm
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	USB interface
Interface	USB interface
Measurement technology	digital
Packaging	sturdy box
Type of product	micrometer