

Mitutoyo
Digital external micrometer large, Measuring range: 150-300 mm

Order data

Order number	421558 150-300
GTIN	4946368695891
Item class	44A

Description
Version:

Hardened and ground measuring spindle and measuring faces; locked by locking lever. With ratchet. **6 easily interchangeable measuring anvils give a measuring range of 150 mm per set.**

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Accuracy:

$(4 + L / 75) \mu\text{m}$

Supplied with:

Measuring spindles, setting standards, 1 battery No. 081560 size 357.

Optional extras:

Data cable No. 497445.

Packaging: sturdy box

IP Index of Protection: IP 65

Calibration: S3

Scale divisions: 0.001 mm

Spindle Ø: 6.35 mm

Spindle pitch: 0.5 mm

Spindle travel: 25 mm

Barrel Ø: 18 mm

Weight: 1.88 kg

Technical description

Number of micrometer standards	6
Spindle pitch	0.5 mm
Spindle travel	25 mm
Spindle Ø	6.35 mm
Barrel Ø	18 mm
Measuring range	150 - 300 mm
Weight	1.88 kg
Scale divisions	0.001 mm
Calibration	S3
Article no of the battery / rechargeable battery fitted	081560 357
Number of batteries contained	1
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	DIN 863
Interface	USB interface
Interface	Digimatic interface
Measurement technology	digital
Packaging	sturdy box
Type of product	micrometer

Services

Calibration External micrometers with extensions Measuring range 150-300 mm	011210 150-300
Labelling laser-etched Type	018940
Calibration External micrometers with extensions Measuring range 150-300 mm	020450 150-300

Accessories

Button cell / special battery Battery type 357	081560 357
--	------------

Connecting cable with data switch Type D2	497445 D2
Connecting cable with data switch Type USB2	497445 USB2
Connecting cable with data switch Type D1	497445 D1
Transmitter Type S16E	498966 S16E
Multi-receiver / USB keyboard interface Type	498975
Receiver / USB keyboard interface Type	498965