



Digital external micrometer i-wi with sliding spindle, Measuring range: 0-25 mm



Order data

Order number	421605 0-25
GTIN	4059192058845
Item class	43A

Description

Version:

Innovative external micrometer with **10 mm tall characters** on sharp contrast display. Practical HOLD function for freezing the measured value for reliable, error-free reading. Measuring spindle hardened and ground. Carbide anvils. High performance ratchet with quick operation. Painted steel frame with thermal insulation. Button for changeover between relative and absolute measurement. Zero setting in any position. A well-arranged **tolerance display with additional warning limits** allows the user to recognise whether the workpiece is within the tolerance limits.

Description:

- **Spindle pitch 5 mm per revolution reduces the approach time.**
- **Non-rotating spindle protects the surfaces being measured.**

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

1 battery No. 081560 size CR2032, 1 setting standard from size 25-50.

Optional extras:

i-wi radio receiver No. 498912 STICK.

Packaging: sturdy box

IP Index of Protection: IP 65

Calibration: B1

Scale divisions: 0.001 mm

Scale divisions: 0.00005 inch

Error limit: 2 µm

Spindle Ø: 6.5 mm

Spindle pitch: 5 mm

Technical description

Measuring range	0 - 25 mm
Digit height LCD display	10 mm
Spindle pitch	5 mm
Error limit	2 µm
Scale divisions	0.001 mm
Number of batteries contained	1
Scale divisions	0.00005 inch
Spindle Ø	6.5 mm
Calibration	B1
Article no of the battery / rechargeable battery fitted	081560 CR2032
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	MAHR i-wi radio system
Measured value saving	MAHR Reference Lock system
Measurement technology	digital
Packaging	sturdy box
Type of product	micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Labelling laser-etched Type	018940

Accessories

Radio receivers for Mahr i-wi Type STICK

498912 STICK