

Mitutoyo
Digital external micrometer for curved surfaces, Measuring range: 0-25 mm

Order data

| | |
|--------------|---------------|
| Order number | 421630 0-25 |
| GTIN | 4946368689302 |
| Item class | 44A |

Description
Version:

Clear (7.5 mm high), digital measured value display provides quick readings. Addition reading by vernier. Sintered, precision lapped, carbide tipped anvils, measuring spindle hardened and ground. Locking by clamping screw. Measuring force at the ratchet 5 - 10 N.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

From size 25-50 including 1 setting standard. 1 battery No. 081560 size 357.

Optional extras:

Data cable No. 497445.

Packaging: sturdy box

IP Index of Protection: IP 65

Calibration: B1

Technical description

| | |
|---|-----------------|
| Measuring range | 0 - 25 mm |
| Calibration | B1 |
| Number of batteries contained | 1 |
| Article no of the battery / rechargeable battery fitted | 081560 357 |
| IP Index of Protection | IP 65 |
| Power supply | Battery-powered |

| | |
|------------------------|-----------------------------|
| Standard | DIN 863 |
| Interface | USB interface |
| Interface | Digimatic interface |
| Measurement technology | digital |
| Packaging | sturdy box |
| Type of product | Special external micrometer |

Services

| | |
|--|------------|
| Calibration External tube micrometer maximum measuring range 25 mm | 012050 25 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration External micrometer maximum measuring range 100 mm | 012060 100 |
| Calibration External tube micrometer maximum measuring range 25 mm | 022000 25 |
| DAkkS calibration External micrometer maximum measuring range 100 mm | 022010 100 |

Accessories

| | |
|--|-------------|
| Button cell / special battery Battery type 357 | 081560 357 |
| Multi-receiver / USB keyboard interface Type | 498975 |
| Connecting cable with data switch Type D2 | 497445 D2 |
| Transmitter Type S16E | 498966 S16E |
| Connecting cable with data switch Type D1 | 497445 D1 |
| Connecting cable with data switch Type USB2 | 497445 USB2 |
| Receiver / USB keyboard interface Type | 498965 |