

Mitutoyo
Digital external micrometer for thread measurements, Measuring range: 0-25 mm

Order data

Order number	421650 0-25
GTIN	4946368695761
Item class	44A

Description
Version:

Clear (7.5 mm high), digital measured value display provides quick readings. Addition reading by vernier. Sintered, precision lapped, carbide tipped anvils, measuring spindle hardened and ground. Locking by clamping screw. Measuring force at the ratchet 5 - 10 N.

Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

From size 25-50 including 1 setting standard. 1 battery No. 081560 size 357.

Without setting standards.
Optional extras:

Data cable No. 497445.

Anvils for thread measurement No. 421652.

Packaging: sturdy box

IP Index of Protection: IP 65

Calibration: B1

Technical description

Measuring range	0 - 25 mm
Calibration	B1
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 357

IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	DIN 863
Interface	USB interface
Interface	Digimatic interface
Measurement technology	digital
Packaging	sturdy box
Type of product	Special external micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 25 mm	022000 25

Accessories

Multi-receiver / USB keyboard interface Type	498975
Pair of anvils for external thread micrometers Pitch 2-3 mm	421652 2-3
Button cell / special battery Battery type 357	081560 357
Pair of anvils for external thread micrometers Pitch 0,6-0,9 mm	421652 0,6-0,9
Pair of anvils for external thread micrometers Pitch 5,5-7 mm	421652 5,5-7
Connecting cable with data switch Type D2	497445 D2
Pair of anvils for external thread micrometers Pitch 1-1,75 mm	421652 1-1,75
Connecting cable with data switch Type USB2	497445 USB2
Transmitter Type S16E	498966 S16E
Connecting cable with data switch Type D1	497445 D1
Receiver / USB keyboard interface Type	498965

Pair of anvils for external thread micrometers Pitch 0,4-0,5
mm

421652 0,4-0,5

Pair of anvils for external thread micrometers Pitch 3,5-5
mm

421652 3,5-5