



## Digital external micrometer i-wi for measuring slots, Measuring range: 75-100 mm



### Order data

Order number	421695 75-100
GTIN	4059192058913
Item class	43A

### Description

#### Version:

Innovative external micrometer with **10 mm tall characters** on sharp contrast display. Practical HOLD function for freezing the measured value for reliable, error-free reading. Painted steel frame with thermal insulation. Button for changeover between relative and absolute measurement. Zero setting in any position. A well-arranged **tolerance display with additional warning limits** allows the user to recognise whether the workpiece is within the tolerance limits. Non-rotating spindle. **QUICK DRIVE** with **spindle pitch of 5 mm** per revolution.

#### Function:

IP65: Protected against jets of water from all directions and protected against penetration by dust (dust-tight), also completely protected against touching.

#### Supplied with:

1 battery No. 081560 size CR2032, 1 setting standard from size 25-50.

#### Optional extras:

i-wi radio receiver No. 498912.

Reversible reading: mm / inch

IP Index of Protection: IP 65

Calibration: B1

Calibration: B2

Scale divisions: 0.001 mm

Scale divisions: 0.00005 inch

Spindle pitch: 5 mm

Error limit: 5 µm

### Technical description

Scale divisions	0.001 mm
Digit height LCD display	10 mm
Calibration	B1
Calibration	B2
Error limit	5 µm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Scale divisions	0.00005 inch
Spindle pitch	5 mm
IP Index of Protection	IP 65
Power supply	Battery-powered
Standard	Manufacturer's standard
Interface	MAHR i-wi radio system
Measurement technology	digital
Packaging	sturdy box
Reversible reading	mm / inch
Type of product	Special external micrometer