



Digital external micrometer with offset measuring faces, Måleområde: 0-25 mm



Order data

Order number	421720 0-25
GTIN	4045197928795
Item class	42B

Description

Version:

Easy to read digital display with additional analogue reading. Robust metal casing. Rotating measurement spindle, carbide-tipped measuring faces

Function:

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

Supplied with:

1 battery No. 081560 size 357

Micrometer barrel graduations: 1/50

IP Index of Protection: IP 54

Calibration: B1

Scale divisions: 0.001 mm

Scale divisions: 0.00005 inch

Error limit: 4 µm

Technical description

Article no of the battery / rechargeable battery fitted	081560 357
Number of batteries contained	1
Calibration	B1
Scale divisions	0.001 mm
Scale divisions	0.00005 inch

Error limit	4 µm
IP Index of Protection	IP 54
Power supply	Battery-powered
Standard	DIN 863
Measurement technology	digital
Packaging	sturdy box
Reversible reading	mm / inch
Micrometer barrel graduations	1/50
Type of product	Special external micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Labelling laser-etched Type	018940

Accessories

Button cell / special battery Battery type 357	081560 357
--	------------