



## External blade micrometer, Measuring range: 0-25 mm



### Order data

Order number	421900 0-25
GTIN	4045197203953
Item class	42B

### Description

#### Version:

With non-rotating spindle and flat blade anvils. Measuring spindle and anvil of hardened steel, controls and reading parts satin chrome-plated.

#### Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.01 mm

Spindle Ø: 8 mm

Spindle pitch: 0.5 mm

Flat blade anvils width: 0.75 mm

Flat blade anvils length: 6.5 mm

### Technical description

Spindle Ø	8 mm
Micrometer barrel graduations	1/50 mm
Measuring range	0 - 25 mm
Flat blade anvils length	6.5 mm
Spindle pitch	0.5 mm
Flat blade anvils width	0.75 mm

Scale divisions	0.01 mm
Calibration	B1
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

### Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 25 mm	022000 25
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100