

Mitutoyo
External micrometer with Vee-anvil, Measuring range: 10-25 mm

Order data

Order number	422300 10-25
GTIN	4946368009971
Item class	44A

Description
Version:

With Vee anvil for measuring three or five-flute cutters. Enamelled frame. Spindle pitch correction for Vee angle. **Triangular** with a Vee angle of 60°.

Application:

For measuring **3 or 5 flute cutters** (end mills, reamers).

Supplied with:

Setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Calibration: B8

Scale divisions: 0.01 mm

Spindle Ø: 6.35 mm

Barrel Ø: 18 mm

Vee angle: 60 (triangular) degrees

Technical description

Measuring range	10 - 25 mm
Spindle Ø	6.35 mm
Barrel Ø	18 mm
Vee angle	60 (triangular) degrees
Micrometer barrel graduations	1/50 mm

Scale divisions	0.01 mm
Calibration	B1
Calibration	B8
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
Calibration Micrometer standard for external thread micrometers maximum nominal size 100 mm	012380 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 25 mm	022000 25
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration Micrometer standard for external thread micrometers maximum nominal size 100 mm	022330 100