



## Thread measurement wires set, Wire $\varnothing$ : 1,100 mm



### Order data

Order number	422490 1,100
GTIN	2050001063557
Item class	46P

### Description

#### IMPORTANT: item is configurable

##### Version:

The thread measurement wires are hardened and precision lapped, the holders are matt chrome-plated. A snap ring in the mounting bore ensures secure easy-twist seating on the measuring spindle.

**When ordering, please specify the  $\varnothing$  of the measuring spindle** (6.35 mm / 6.5 mm / 6.8 mm / 7.5 mm / 8.0 mm).

##### Application:

For determining the flank  $\varnothing$  of external threads using the three-wire method in conjunction with an external micrometer or a length measurement bench.

##### Supplied with:

A set consists of a holder with one measurement wire and a holder with two measurement wires, in a plastic box.

Calibration: L16

Error limit:  $\pm 1 \mu\text{m}$

for threads: M12

for thread pitch P: 1.75

Check gauge M to DIN 13 sheet 1: 12.650 mm

### Technical description

Check gauge M to DIN 13 sheet 1	12.650 mm
---------------------------------	-----------

for thread pitch P	1.75
Wire Ø	1.1 mm
for threads	M12
Error limit	±1 µm
Packaging	sturdy box
Calibration	L16
Type of product	Thread measurement wire (pair)
for spindle Ø	6.35 mm
for spindle Ø	6.5 mm
for spindle Ø	6.8 mm
for spindle Ø	7.5 mm
for spindle Ø	8 mm

## Services

Calibration Thread measurement wire	018780
Labelling laser-etched Type	018940
DAkkS calibration Thread measurement wire	019160
Calibration Thread measurement wire Type GMD	028900 GMD
DAkkS calibration Thread measurement wire Type GMD	028910 GMD