

 Mahr**Micrometer with dial comparator, Measuring range: 0-25 mm****Order data**

Order number	422500 0-25
GTIN	4059192004248
Item class	43A

Description**Version:**

Measuring spindle through hardened and ground.

With precision lapped **carbide tipped anvils**.

Spindle and anvil of stainless steel.

One piece frame and spindle guide.

Button for retracting the measurement anvil for repetitive measurements.

With adjustment screw for zeroing.

Tolerance pointers for good/ reject measurements.

With hand temperature protection. Lever for spindle clamping.

Callout:

Deviation read-off in 1/1000 mm.

Push button for anvil retraction.

Accuracy:

Dial comparator 1 μm – micrometer 2 μm .

Calibration: B9

Measuring range dial comparator: ± 0.065 mm

Graduation of the micrometer: 0.01 mm

Graduation of the precision dial comparator: 0.001 mm

Clearance depth of micrometer frame: 16 mm

Technical description

Measuring range dial comparator	±0.065 mm
Measuring range	0 - 25 mm
Clearance depth of micrometer frame	16 mm
Graduation of the precision dial comparator	0.001 mm
Graduation of the micrometer	0.01 mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B9
Type of product	Micrometer with dial comparator

Services

Calibration Indicator micrometer maximum measuring range 25 mm	012240 25
Labelling laser-etched Type	018940
Calibration Indicator micrometer maximum measuring range 25 mm	022100 25