



## Micrometer with dial comparator, Measuring range: 50-75 mm



### Order data

Order number	422501 50-75
GTIN	2050001774453
Item class	46P

### Description

#### Version:

Measuring spindle through hardened and ground.  
 With precision lapped **carbide tipped anvils**.  
 Spindle and anvil of stainless steel.  
 One piece frame and spindle guide.  
 Button for retracting the measurement anvil for repetitive measurements.  
 With adjustment screw for zeroing.  
 Tolerance pointers for good/ reject measurements.  
 With hand temperature protection. Lever for spindle clamping.

#### Callout:

Deviation read-off in 1/1000 mm.  
 Push button for anvil retraction.

#### Accuracy:

**Dial comparator 2 µm – micrometer 2 µm.**

#### Supplied with:

Adjustment wrench.

#### Note:

Measuring faces of CBN on request.  
 Calibration: B9  
 Measuring range dial comparator:  $\pm 0.14$  mm  
 Graduation of the micrometer: 0.01 mm  
 Graduation of the precision dial comparator: 0.002 mm  
 Clearance depth of micrometer frame: 37.5 mm

## Technical description

Measuring range	50 - 75 mm
Graduation of the precision dial comparator	0.002 mm
Clearance depth of micrometer frame	37.5 mm
Graduation of the micrometer	0.01 mm
Measuring range dial comparator	$\pm 0.14$ mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B9
Type of product	Micrometer with dial comparator

## Services

Calibration Indicator micrometer maximum measuring range 200 mm	012240 200
Labelling laser-etched Type	018940
Calibration Indicator micrometer maximum measuring range 200 mm	022100 200