



External micrometer with disc anvils \varnothing 30 mm, Measuring range: 125-150 mm



Order data

Order number	422992 125-150
GTIN	4250099616552
Item class	46P

Description

Version:

Disc anvil of hardened steel in flat version, **without recess**. Hardened and ground measuring spindle. Higher accuracy than **DIN 863**. Locking by clamping device. With ratchet and hand temperature protection. Clearly engraved black divisions and numerals.

Application:

For determining the tooth widths of spur and helical gears from module 0.6.

Packaging: sturdy box

Micrometer barrel graduations: 1/100 mm

Calibration: B1

Scale divisions: 0.01 mm

Error limit: 6 μ m

Spindle \varnothing : 8 mm

Barrel \varnothing : 24 mm

Technical description

Calibration	B1
Locking	by clamping device
Type of spindle	hardened and ground
Micrometer barrel graduations	1/100 mm
Barrel \varnothing	24 mm

Type of reading parts	engraved, black
Type of operating parts	Hand temperature protection
Measuring range	125 - 150 mm
Scale divisions	0.01 mm
Spindle Ø	8 mm
Error limit	6 µm
Standard	Manufacturer's standard
Ratchet	yes
Disc anvil	yes
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

Services

Calibration External tube micrometer maximum measuring range 200 mm	012050 200
Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	012110 300
Labelling laser-etched Type 900	018940
Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	022090 900
Calibration External tube micrometer maximum measuring range 200 mm	022080 300
Calibration External tube micrometer maximum measuring range 200 mm	022000 200