



External micrometer with disc anvils, Measuring range: 0-25 mm



Order data

Order number	423000 0-25
GTIN	4045197204004
Item class	42B

Description

Version:

With large-area, hardened disc anvils. Forged and enamelled frame.
Design with rotating spindle.

Application:

For determining the tooth widths of spur and helical gears from module 0.8.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.01 mm

Parallelism of the measuring faces: 5 μ m

Spindle \varnothing : 8 mm

Spindle pitch: 0.5 mm

Disc anvil \varnothing : 20 mm

Technical description

Disc anvil \varnothing	20 mm
Parallelism of the measuring faces	5 μ m
Micrometer barrel graduations	1/50 mm

Measuring range	0 - 25 mm
Spindle Ø	8 mm
Spindle pitch	0.5 mm
Scale divisions	0.01 mm
Calibration	B1
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration External tube micrometer maximum measuring range 25 mm	022000 25