



## External micrometer with disc anvils, Measuring range: 125-150 mm



### Order data

Order number	423000 125-150
GTIN	4045197204059
Item class	42B

### Description

#### Version:

With large-area, hardened disc anvils. Forged and enamelled frame.  
Design with rotating spindle.

#### Application:

For determining the tooth widths of spur and helical gears from module 0.8.

#### Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Calibration: B2

Scale divisions: 0.01 mm

Parallelism of the measuring faces: 6 µm

Spindle Ø: 8 mm

Spindle pitch: 0.5 mm

Disc anvil Ø: 30 mm

### Technical description

Spindle pitch	0.5 mm
Disc anvil Ø	30 mm

Spindle Ø	8 mm
Micrometer barrel graduations	1/50 mm
Measuring range	125 - 150 mm
Parallelism of the measuring faces	6 µm
Scale divisions	0.01 mm
Calibration	B1
Calibration	B2
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

## Services

Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	012110 300
Calibration External tube micrometer maximum measuring range 200 mm	012050 200
Labelling laser-etched Type	018940
900	022090 900
Calibration External tube micrometer maximum measuring range 200 mm	022000 200
Calibration Micrometer standard for external micrometer maximum nominal size 300 mm	022080 300