



## External micrometer with disc anvils, Measuring range: 25-50 mm



### Order data

Order number	423000 25-50
GTIN	4045197204011
Item class	42B

### Description

#### Version:

With large-area, hardened disc anvils. Forged and enamelled frame.  
Design with rotating spindle.

#### Application:

For determining the tooth widths of spur and helical gears from module 0.8.

#### Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Calibration: B2

Scale divisions: 0.01 mm

Parallelism of the measuring faces: 5 µm

Spindle Ø: 8 mm

Spindle pitch: 0.5 mm

Disc anvil Ø: 20 mm

### Technical description

Parallelism of the measuring faces	5 µm
Spindle Ø	8 mm

Spindle pitch	0.5 mm
Measuring range	25 - 50 mm
Disc anvil Ø	20 mm
Micrometer barrel graduations	1/50 mm
Scale divisions	0.01 mm
Calibration	B1
Calibration	B2
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

## Services

Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100
100	022090 100

## Accessories

Micrometer setting standard overall length 25 mm	421100 25
--	-----------