



External micrometer with disc anvils, Measuring range: 75-100 mm



Order data

Order number	423000 75-100
GTIN	4045197204035
Item class	42B

Description

Version:

With large-area, hardened disc anvils. Forged and enamelled frame.
Design with rotating spindle.

Application:

For determining the tooth widths of spur and helical gears from module 0.8.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Calibration: B2

Scale divisions: 0.01 mm

Parallelism of the measuring faces: 5 µm

Spindle Ø: 8 mm

Spindle pitch: 0.5 mm

Disc anvil Ø: 20 mm

Technical description

Micrometer barrel graduations	1/50 mm
Measuring range	75 - 100 mm

Spindle Ø	8 mm
Disc anvil Ø	20 mm
Parallelism of the measuring faces	5 µm
Spindle pitch	0.5 mm
Scale divisions	0.01 mm
Calibration	B1
Calibration	B2
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

Services

Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
100	022090 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100

Accessories

Micrometer setting standard overall length 75 mm	421100 75
--	-----------