

HOLEX®

External micrometer with disc anvils and non-rotating spindle, Measuring range: 25-50 mm



Order data

Order number	423005 25-50
GTIN	4062406237769
Item class	42B

Description

Version:

With large-area, hardened disc anvils. Forged and enamelled frame.
Design with non-rotating spindle.

Application:

For determining the tooth widths of spur and helical gears from module 0.8.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Parallelism of the measuring faces: 5 µm

Spindle Ø: 8 mm

Spindle pitch: 0.5 mm

Disc anvil Ø: 19.5 mm

Technical description

Parallelism of the measuring faces	5 µm
Micrometer barrel graduations	1/50 mm
Calibration	B2

Calibration	B1
Disc anvil Ø	19.5 mm
Scale divisions	0.01 mm
Spindle Ø	8 mm
Measuring range	25 - 50 mm
Spindle pitch	0.5 mm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

Services

Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Labelling laser-etched Type	018940

Accessories

Micrometer setting standard overall length 25 mm	421100 25
--	-----------