

HOLEX®

External micrometer with disc anvils and non-rotating spindle, Measuring range: 75-100 mm



Order data

Order number	423005 75-100
GTIN	4062406237783
Item class	42B

Description

Version:

With large-area, hardened disc anvils. Forged and enamelled frame.
Design with non-rotating spindle.

Application:

For determining the tooth widths of spur and helical gears from module 0.8.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B2

Calibration: B1

Scale divisions: 0.01 mm

Parallelism of the measuring faces: 5 µm

Spindle Ø: 8 mm

Spindle pitch: 0.5 mm

Disc anvil Ø: 19.5 mm

Technical description

Scale divisions	0.01 mm
Disc anvil Ø	19.5 mm
Calibration	B2

Calibration	B1
Micrometer barrel graduations	1/50 mm
Measuring range	75 - 100 mm
Spindle pitch	0.5 mm
Parallelism of the measuring faces	5 µm
Spindle Ø	8 mm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

Services

Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100

Accessories

Micrometer setting standard overall length 75 mm	421100 75
--	-----------