



## Micrometer with dial comparator, Measuring range: 100-150 mm



### Order data

Order number	424800 100-150
GTIN	2050001036667
Item class	43A

### Description

#### Version:

Measuring spindle of stainless steel, hardened and ground. Carbide-tipped measuring faces. Controls and reading parts satin chrome-plated. With hand temperature protection. Constant measuring force. Moveable stop anvil, retractable. Particularly suitable for series manufactured parts.

#### Accuracy:

**Dial comparator DIN 863 – micrometer 2 µm.**

#### Supplied with:

Dial comparator Millimes No. 434674 size 50/1.

Calibration: C3

Measuring range dial comparator:  $\pm 0.05$  mm

Graduation of the micrometer: 0.01 mm

Graduation of the precision dial comparator: 0.001 mm

Spindle  $\varnothing$ : 7.5 mm

Barrel  $\varnothing$ : 18 mm

### Technical description

Measuring range dial comparator	$\pm 0.05$ mm
Barrel $\varnothing$	18 mm

Graduation of the micrometer	0.01 mm
Graduation of the precision dial comparator	0.001 mm
Spindle Ø	7.5 mm
Measuring range	100 - 150 mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B1
Calibration	C3
Type of product	Micrometer with dial comparator

### Services

Calibration Precision dial comparator	013470
Calibration External tube micrometer maximum measuring range 200 mm	012050 200
Labelling laser-etched Type	018940
DAkkS calibration Precision dial comparator	013450

### Accessories

Precision dial comparator ± measuring range / reading 50/1 µm	434674 50/1
---	-------------