



Micrometer with dial comparator, Measuring range: 150-200 mm



Order data

Order number	424800 150-200
GTIN	2050001036674
Item class	43A

Description

Version:

Measuring spindle of stainless steel, hardened and ground. Carbide-tipped measuring faces. Controls and reading parts satin chrome-plated. With hand temperature protection. Constant measuring force. Moveable stop anvil, retractable. Particularly suitable for series manufactured parts.

Accuracy:

Dial comparator DIN 863 – micrometer 2 µm.

Supplied with:

Dial comparator Millimes No. 434674 size 50/1.

Calibration: C3

Measuring range dial comparator: ±0.05 mm

Graduation of the micrometer: 0.01 mm

Graduation of the precision dial comparator: 0.001 mm

Spindle Ø: 7.5 mm

Barrel Ø: 18 mm

Technical description

Graduation of the micrometer	0.01 mm
Barrel Ø	18 mm

Spindle Ø	7.5 mm
Measuring range dial comparator	±0.05 mm
Measuring range	150 - 200 mm
Graduation of the precision dial comparator	0.001 mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B1
Calibration	C3
Type of product	Micrometer with dial comparator

Services

Calibration External tube micrometer maximum measuring range 200 mm	012050 200
Calibration Precision dial comparator	013470
Labelling laser-etched Type	018940
DAkkS calibration Precision dial comparator	013450
Calibration Precision dial comparator Type FZ	023180 FZ
DAkkS calibration Precision dial comparator Type FZ	023190 FZ
Calibration External tube micrometer maximum measuring range 200 mm	022000 200

Accessories

Precision dial comparator ± measuring range / reading 50/1 µm	434674 50/1
---	-------------