



## Precision bench micrometer, Measuring range: 0-50 mm



### Order data

Order number	424805 0-50
GTIN	4059192004774
Item class	43A

### Description

#### Version:

Strong steel frame, can be inclined up to 45° against sturdy base. Height-adjustable stop. Measuring spindle of stainless steel, hardened and ground. Carbide-tipped measuring faces. Controls and reading parts satin chrome-plated. With hand temperature protection. Constant measuring force. Moveable stop anvil; lifting with retraction lever. Especially suitable for series manufactured parts and quick inspection.

#### Accuracy:

**Dial comparator DIN 863 – micrometer 2 µm.**

#### Supplied with:

Dial comparator Millimes No. 434674 size 50/1.

Calibration: B1

Measuring range dial comparator: ±0.05 mm

Graduation of the micrometer: 0.005 mm

Graduation of the precision dial comparator: 0.001 mm

Spindle Ø: 7.5 mm

Barrel Ø: 25 mm

### Technical description

Graduation of the micrometer	0.005 mm
Measuring range	0 - 50 mm
Barrel Ø	25 mm
Spindle Ø	7.5 mm
Measuring range dial comparator	±0.05 mm
Graduation of the precision dial comparator	0.001 mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Calibration	C3
Calibration	B1
Type of product	Micrometer with dial comparator

## Services

Calibration Precision dial comparator	013470
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
Labelling laser-etched Type	018940
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
DAkkS calibration Precision dial comparator	013450
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100
Calibration Precision dial comparator Type FZ	023180 FZ
DAkkS calibration Precision dial comparator Type FZ	023190 FZ

## Accessories

Precision dial comparator ± measuring range / reading 50/1 µm	434674 50/1
---	-------------

