

Mitutoyo
Micrometer head, Measuring range (travel): 0-13 mm

Order data

Order number	426200 0-13
GTIN	4946368020617
Item class	44A

Description
Version:

Fully hardened spindle and glare-free satin chrome-plated barrel. **Rotating spindle**, without carbide contact face, without ratchet, **short version**.

Application:

For installation in machines, inspection fixtures, measuring instruments etc. as an adjustable comparator stand stop.

Note:

Special sizes on request.
 Calibration: B3
 Scale divisions: 0.01 mm
 Error limit: 0.002 mm
 Spindle Ø: 5 mm
 Barrel Ø: 13 mm
 Mounting shank Ø: 9.5 mm
 Length of mounting shank: 9.5 mm

Technical description

Spindle Ø	5 mm
Mounting shank Ø	9.5 mm
Barrel Ø	13 mm
Length of mounting shank	9.5 mm
Measuring range (travel)	0 - 13 mm
Overall length	58.5 mm

Scale divisions	0.01 mm
Error limit	0.002 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Calibration	B3
Type of product	Micrometer head

Services

Calibration Micrometer head maximum measuring range 25 mm	012600 25
Labelling laser-etched Type	018940
Calibration Micrometer head maximum measuring range 25 mm	022280 25