

Mitutoyo
Micrometer head, Measuring range (travel): 0-25/F mm

Order data

Order number	426200 0-25/F
GTIN	4946368023151
Item class	44A

Description
Version:

Fully hardened spindle and glare-free satin chrome-plated barrel. **Stationary (non-rotating)** spindle with carbide tipped contact face and ratchet. For checking materials with delicate surfaces.

Application:

For installation in machines, inspection fixtures, measuring instruments etc. as an adjustable comparator stand stop.

Note:

Special sizes on request.

Calibration: B3

Scale divisions: 0.01 mm

Error limit: 0.003 mm

Spindle Ø: 8 mm

Barrel Ø: 18 mm

Mounting shank Ø: 12 mm

Length of mounting shank: 10 mm

Technical description

Spindle Ø	8 mm
Mounting shank Ø	12 mm
Barrel Ø	18 mm
Overall length	125 mm
Length of mounting shank	10 mm
Scale divisions	0.01 mm

Error limit	0.003 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Calibration	B3
Type of product	Micrometer head

Services

Calibration Micrometer head maximum measuring range 25 mm	012600 25
Labelling laser-etched Type	018940
Calibration Micrometer head maximum measuring range 25 mm	022280 25