

Mitutoyo
Micrometer head, Measuring range (travel): 0-6,5 mm


Order data

Order number	426200 0-6,5
GTIN	4946368020815
Item class	44A

Description

Version:

Fully hardened spindle and glare-free satin chrome-plated barrel. **Rotating spindle** without carbide contact face, without ratchet, **extra short version, spherical contact face.**

Application:

For installation in machines, inspection fixtures, measuring instruments etc. as an adjustable comparator stand stop.

Note:

Special sizes on request.

Calibration: B3

Scale divisions: 0.01 mm

Error limit: 0.002 mm

Spindle Ø: 3.5 mm

Barrel Ø: 9 mm

Radius contact face: 3 mm

Mounting shank Ø: 6 mm

Technical description

Radius contact face	3 mm
Barrel Ø	9 mm
Measuring range (travel)	0 - 6.5 mm
Spindle Ø	3.5 mm
Length of mounting shank	6 mm
Mounting shank Ø	6 mm

Overall length	37 mm
Scale divisions	0.01 mm
Error limit	0.002 mm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Calibration	B3
Type of product	Micrometer head

Services

Calibration Micrometer head maximum measuring range 25 mm	012600 25
Labelling laser-etched Type	018940
Calibration Micrometer head maximum measuring range 25 mm	022280 25