

Mitutoyo
Digital micrometer head with data output, Measuring range (travel): 0-50 mm


Order data

| | |
|--------------|---------------|
| Order number | 426510 0-50 |
| GTIN | 4946368610276 |
| Item class | 44A |

Description

Version:

Direct reading from clear digital display. Reliable and error-free measurements - without a vernier. Hardened and ground measuring spindle, locking by clamping screw, ratchet.

Application:

For installation in machines, inspection fixtures, measuring instruments etc. as an adjustable micrometer stop.

Supplied with:

1 battery No. 081560 size 357.

Optional extras:

Data cable No. 497100.

Calibration: B3

Scale divisions: 0.001 mm

Error limit: 0.003 mm

Spindle Ø: 11 mm

Barrel Ø: 49 mm

Mounting shank Ø: 18 mm

Length of mounting shank: 14 mm

Technical description

| | |
|--------------------------|-----------|
| Length of mounting shank | 14 mm |
| Spindle Ø | 11 mm |
| Overall length | 172 mm |
| Measuring range (travel) | 0 - 50 mm |

| | |
|---|-------------------------|
| Mounting shank Ø | 18 mm |
| Barrel Ø | 49 mm |
| Scale divisions | 0.001 mm |
| Error limit | 0.003 mm |
| Article no of the battery / rechargeable battery fitted | 081560 357 |
| Number of batteries contained | 1 |
| Power supply | Battery-powered |
| Standard | Manufacturer's standard |
| Interface | Digimatic interface |
| Interface | USB interface |
| Measurement technology | digital |
| Calibration | B3 |
| Type of product | Micrometer head |

Services

| | |
|--|------------|
| Calibration Micrometer head maximum measuring range 100 mm | 012600 100 |
| Labelling laser-etched Type | 018940 |
| Calibration Micrometer head maximum measuring range 100 mm | 022280 100 |

Accessories

| | |
|--|-------------|
| Connecting cable Type D1 | 497080 D1 |
| Transmitter Type S1 | 498966 S1 |
| Connecting cable with data switch Type D1 | 497100 D1 |
| Multi-receiver / USB keyboard interface Type | 498975 |
| Connecting cable with data switch Type D2 | 497100 D2 |
| Connecting cable with data switch Type USB2 | 497100 USB2 |
| Connecting cable Type D2 | 497080 D2 |
| Receiver / USB keyboard interface Type | 498965 |

Connecting cable Type USB2

497080 USB2