



## Internal micrometer, Measuring range: 50-75 mm



### Order data

Order number	426800 50-75
GTIN	4045197204141
Item class	42B

### Description

#### Version:

Fully hardened, ground and lapped spindle. Offset and rounded jaw ends with carbide tips. Constant measuring force due to precision ratchet. Barrel with clearly engraved, black graduations. Satin chrome-plated micrometer. With adjusting screw and locking screw.

#### Supplied with:

Supplied with setting ring for adjustment.

Calibration: M3

Scale divisions: 0.01 mm

Error limit: 14 µm

Barrel Ø: 18 mm

### Technical description

Measuring range	50 - 75 mm
Barrel Ø	18 mm
Scale divisions	0.01 mm
Error limit	14 µm
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B4

Calibration	M3
Type of product	Internal micrometer

## Services

Calibration Internal micrometer maximum measuring range 75 mm	012700 75
Calibration Setting ring maximum Ø 100 mm	018430 100
Labelling laser-etched Type	018940
DAkkS calibration Setting ring maximum Ø 200 mm	019660 200
Calibration Setting ring maximum Ø 100 mm	028400 100
DAkkS calibration Setting ring maximum Ø 200 mm	028470 200
Calibration Internal micrometer maximum measuring range 75 mm	022360 75

## Accessories

Setting ring DIN 2250 C Nominal size Ø 70 mm	484030 70
Setting ring DIN 2250 C Nominal size Ø 60 mm	484030 60
Setting ring DIN 2250 C Nominal size Ø 75 mm	484030 75