

**Mitutoyo**
**Internal micrometer, Measuring range: 25-50 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 426805 25-50  |
| GTIN         | 4946368019888 |
| Item class   | 44A           |

**Description**
**Version:**

Fully hardened, ground and lapped spindle. Offset and rounded jaw ends with carbide tips. Constant measuring force due to precision ratchet. Barrel with clearly engraved, black graduations. Satin chrome-plated micrometer. With adjusting screw and locking screw.

**Optional extras:**

Setting ring No. 484030.

Calibration: B4

Scale divisions: 0.01 mm

Error limit: 6 µm

Barrel Ø: 18 mm

**Technical description**

|                               |                         |
|-------------------------------|-------------------------|
| Measuring range               | 25 - 50 mm              |
| Barrel Ø                      | 18 mm                   |
| Scale divisions               | 0.01 mm                 |
| Error limit                   | 6 µm                    |
| Standard                      | Manufacturer's standard |
| Micrometer barrel graduations | 1/50 mm                 |
| Measurement technology        | analogue                |
| Packaging                     | sturdy box              |

|                 |                     |
|-----------------|---------------------|
| Calibration     | B4                  |
| Type of product | Internal micrometer |

## Services

|   |           |
|---|-----------|
| Calibration Internal micrometer maximum measuring range 50 mm | 012700 50 |
| Labelling laser-etched Type                                   | 018940    |
| Calibration Internal micrometer maximum measuring range 50 mm | 022360 50 |

## Accessories

|  |           |
|--|-----------|
| Setting ring DIN 2250 C Nominal size Ø 32 mm | 484030 32 |
| Setting ring DIN 2250 C Nominal size Ø 46 mm | 484030 46 |
| Setting ring DIN 2250 C Nominal size Ø 30 mm | 484030 30 |
| Setting ring DIN 2250 C Nominal size Ø 38 mm | 484030 38 |
| Setting ring DIN 2250 C Nominal size Ø 44 mm | 484030 44 |
| Setting ring DIN 2250 C Nominal size Ø 42 mm | 484030 42 |
| Setting ring DIN 2250 C Nominal size Ø 26 mm | 484030 26 |
| Setting ring DIN 2250 C Nominal size Ø 35 mm | 484030 35 |
| Setting ring DIN 2250 C Nominal size Ø 40 mm | 484030 40 |
| Setting ring DIN 2250 C Nominal size Ø 36 mm | 484030 36 |
| Setting ring DIN 2250 C Nominal size Ø 45 mm | 484030 45 |
| Setting ring DIN 2250 C Nominal size Ø 34 mm | 484030 34 |
| Setting ring DIN 2250 C Nominal size Ø 28 mm | 484030 28 |
| Setting ring DIN 2250 C Nominal size Ø 25 mm | 484030 25 |
| Setting ring DIN 2250 C Nominal size Ø 50 mm | 484030 50 |