

Mitutoyo
Internal micrometer, Measuring range: 50-75 mm

Order data

Order number	426805 50-75
GTIN	4946368019895
Item class	44A

Description
Version:

Fully hardened, ground and lapped spindle. Offset and rounded jaw ends with carbide tips. Constant measuring force due to precision ratchet. Barrel with clearly engraved, black graduations. Satin chrome-plated micrometer. With adjusting screw and locking screw.

Optional extras:

Setting ring No. 484030.

Calibration: B4

Scale divisions: 0.01 mm

Error limit: 7 μ m

Barrel \varnothing : 18 mm

Technical description

Barrel \varnothing	18 mm
Measuring range	50 - 75 mm
Scale divisions	0.01 mm
Error limit	7 μ m
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B4

Type of product	Internal micrometer
-----------------	---------------------

Services

Calibration Internal micrometer maximum measuring range 75 mm	012700 75
Labelling laser-etched Type	018940
Calibration Internal micrometer maximum measuring range 75 mm	022360 75

Accessories

Setting ring DIN 2250 C Nominal size Ø 75 mm	484030 75
Setting ring DIN 2250 C Nominal size Ø 70 mm	484030 70
Setting ring DIN 2250 C Nominal size Ø 50 mm	484030 50
Setting ring DIN 2250 C Nominal size Ø 65 mm	484030 65
Setting ring DIN 2250 C Nominal size Ø 55 mm	484030 55
Setting ring DIN 2250 C Nominal size Ø 60 mm	484030 60