

**Mitutoyo**
**Internal micrometer, Measuring range: 75-100 mm**

**Order data**

Order number	426805 75-100
GTIN	4946368019901
Item class	44A

**Description**
**Version:**

Fully hardened, ground and lapped spindle. Offset and rounded jaw ends with carbide tips. Constant measuring force due to precision ratchet. Barrel with clearly engraved, black graduations. Satin chrome-plated micrometer. With adjusting screw and locking screw.

**Optional extras:**

Setting ring No. 484030.

Calibration: B4

Scale divisions: 0.01 mm

Error limit: 8  $\mu$ m

Barrel  $\varnothing$ : 18 mm

**Technical description**

Barrel $\varnothing$	18 mm
Measuring range	75 - 100 mm
Scale divisions	0.01 mm
Error limit	8 $\mu$ m
Standard	Manufacturer's standard
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B4

Type of product	Internal micrometer
-----------------	---------------------

## Services

Calibration Internal micrometer maximum measuring range 100 mm	012700 100
Labelling laser-etched Type	018940
Calibration Internal micrometer maximum measuring range 100 mm	022360 100

## Accessories

Setting ring DIN 2250 C Nominal size Ø 125 mm	484030 125
Setting ring DIN 2250 C Nominal size Ø 275 mm	484030 275
Setting ring DIN 2250 C Nominal size Ø 85 mm	484030 85
Setting ring DIN 2250 C Nominal size Ø 175 mm	484030 175
Setting ring DIN 2250 C Nominal size Ø 225 mm	484030 225
Setting ring DIN 2250 C Nominal size Ø 80 mm	484030 80
Setting ring DIN 2250 C Nominal size Ø 95 mm	484030 95
Setting ring DIN 2250 C Nominal size Ø 100 mm	484030 100
Setting ring DIN 2250 C Nominal size Ø 75 mm	484030 75
Setting ring DIN 2250 C Nominal size Ø 90 mm	484030 90