



## Internal micrometer, Measuring range: 125-150 mm



### Order data

Order number	427800 125-150
GTIN	2050001053657
Item class	43A

### Description

#### Version:

**Lightweight, kink-proof tubular construction.** Measuring spindle through hardened and ground. **Measuring faces hardened and spherical lapped.** Control elements and reading parts satin chrome-plated. From measuring range 100 - 125 mm with thermal insulation and locking lever.

#### Supplied with:

Micrometer in a sleeve.  
 Calibration: B10  
 Scale divisions: 0.01 mm  
 Error limit: 6 µm  
 Spindle Ø: 8 mm  
 Barrel Ø: 20 mm

### Technical description

Spindle Ø	8 mm
Barrel Ø	20 mm
Measuring range	125 - 150 mm
Scale divisions	0.01 mm
Error limit	6 µm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue

Calibration	B10
Type of product	2-point internal micrometer

**Services**

Calibration Internal micrometer maximum measuring range 200 mm	012750 200
Labelling laser-etched Type	018940
DAkkS calibration Internal micrometer maximum measuring range 200 mm	012710 200
DAkkS calibration Internal micrometer maximum measuring range 200 mm	022450 200
Calibration Internal micrometer maximum measuring range 200 mm	022440 200