



## Internal micrometer, Measuring range: 30-40 mm



### Order data

Order number	427800 30-40
GTIN	2050001038067
Item class	43A

### Description

#### Version:

**Lightweight, kink-proof tubular construction.** Measuring spindle through hardened and ground. **Measuring faces hardened and spherical lapped.** Control elements and reading parts satin chrome-plated. From measuring range 100 - 125 mm with thermal insulation and locking lever.

#### Supplied with:

Micrometer in a sleeve.

Calibration: B10

Scale divisions: 0.01 mm

Error limit: 4  $\mu$ m

Spindle  $\varnothing$ : 7 mm

Barrel  $\varnothing$ : 12.5 mm

### Technical description

Barrel $\varnothing$	12.5 mm
Spindle $\varnothing$	7 mm
Measuring range	30 - 40 mm
Scale divisions	0.01 mm
Error limit	4 $\mu$ m
Standard	DIN 863

Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Calibration	B10
Type of product	2-point internal micrometer

## Services

Calibration Internal micrometer maximum measuring range 100 mm	012750 100
Labelling laser-etched Type	018940
DAkkS calibration Internal micrometer maximum measuring range 200 mm	012710 200
Calibration Internal micrometer maximum measuring range 100 mm	022440 100
DAkkS calibration Internal micrometer maximum measuring range 200 mm	022450 200