



Internal micrometer, Measuring range: 70-100 mm



Order data

Order number	427800 70-100
GTIN	4059192005665
Item class	43A

Description

Version:

Lightweight, kink-proof tubular construction. Measuring spindle through hardened and ground. **Measuring faces hardened and spherical lapped.** Control elements and reading parts satin chrome-plated. From measuring range 100 - 125 mm with thermal insulation and locking lever.

Supplied with:

Micrometer in a sleeve.

Calibration: B10

Scale divisions: 0.01 mm

Error limit: 5 μ m

Spindle \varnothing : 7 mm

Barrel \varnothing : 13.5 mm

Technical description

Barrel \varnothing	13.5 mm
Measuring range	70 - 100 mm
Spindle \varnothing	7 mm
Scale divisions	0.01 mm
Error limit	5 μ m
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue

Calibration	B10
Type of product	2-point internal micrometer

Services

Calibration Internal micrometer maximum measuring range 100 mm	012750 100
Labelling laser-etched Type	018940
DAkkS calibration Internal micrometer maximum measuring range 200 mm	012710 200
Calibration Internal micrometer maximum measuring range 100 mm	022440 100
DAkkS calibration Internal micrometer maximum measuring range 200 mm	022450 200