



## XT internal micrometer set, Measuring range: 10-20 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 428550 10-20  |
| GTIN         | 5051102212131 |
| Item class   | 46B           |

### Description

#### Version:

3-Point **XT inside micrometers**. Measuring spindle hardened and ground. Micrometer barrel with black scale, all reading parts satin chrome-plated. Ratchet for consistent measuring force. All gauges supplied with serial number and test certificate. "Micro" - version with better resolution of 2 µm.

#### Application:

Blind holes and through holes, centring edges.

#### Supplied with:

Internal micrometers No. 428500 and setting rings with UKAS test certificate.

#### Optional extras:

Setting rings No. 484030, extension No. 428510.

#### Spare part:

Micrometer heads No. 428605.

Calibration: S6

Number of micrometers: 3

Number of setting rings: 2

Setting ring Ø: 12.5 / 20 mm

### Technical description

|                         |   |
|-------------------------|---|
| Number of setting rings | 2 |
|-------------------------|---|

|                               |                              |
|-------------------------------|------------------------------|
| Measuring range               | 10 - 20 mm                   |
| Setting ring Ø                | 12.5 / 20 mm                 |
| Number of micrometers         | 3                            |
| Standard                      | DIN 863                      |
| Micrometer barrel graduations | 1/50 mm                      |
| Measurement technology        | analogue                     |
| Packaging                     | sturdy box                   |
| Calibration                   | S6                           |
| Type of product               | 3-point internal micrometers |

## Services

|  |              |
|--|--------------|
| Calibration Internal micrometer set Measuring range 10-20 mm | 011240 10-20 |
| Labelling laser-etched Type                                  | 018940       |
| Calibration Internal micrometer set Measuring range 10-20 mm | 020550 10-20 |

## Accessories

|  |                |
|--|----------------|
| XT internal micrometer Measuring range 10-12,5 mm        | 428500 10-12,5 |
| XT internal micrometer Measuring range 16-20 mm          | 428500 16-20   |
| Replacement XT measuring head Measuring range 10-12,5 mm | 428605 10-12,5 |
| XT internal micrometer Measuring range 12,5-16 mm        | 428500 12,5-16 |
| Setting ring DIN 2250 C Nominal size Ø 14 mm             | 484030 14      |
| Setting ring DIN 2250 C Nominal size Ø 18 mm             | 484030 18      |
| Replacement XT measuring head Measuring range 12,5-16 mm | 428605 12,5-16 |
| Extension for internal micrometers Type 3/100            | 428510 3/100   |
| Setting ring DIN 2250 C Nominal size Ø 11 mm             | 484030 11      |
| Extension for internal micrometers Type 2/76             | 428510 2/76    |

Replacement XT measuring head Measuring range 16-20  
mm

---

428605 16-20