



XT internal micrometer set, Measuring range: 20-50 mm



Order data

Order number	428550 20-50
GTIN	5051102071370
Item class	46B

Description

Version:

3-Point **XT inside micrometers**. Measuring spindle hardened and ground. Micrometer barrel with black scale, all reading parts satin chrome-plated. Ratchet for consistent measuring force. All gauges supplied with serial number and test certificate.

Application:

Blind holes and through holes, centring edges.

Supplied with:

Internal micrometers No. 428500 and setting rings with UKAS test certificate.

Optional extras:

Setting rings No. 484030, extension No. 428510.

Spare part:

Micrometer heads No. 428605.

Calibration: S6

Number of micrometers: 3

Number of setting rings: 2

Setting ring \varnothing : 20 / 35 mm

Technical description

Measuring range	20 - 50 mm
-----------------	------------

Number of setting rings	2
Number of micrometers	3
Setting ring Ø	20 / 35 mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometers

Services

Calibration Internal micrometer set Measuring range 20-50 mm	011240 20-50
Labelling laser-etched Type	018940
Calibration Internal micrometer set Measuring range 20-50 mm	020550 20-50

Accessories

Setting ring DIN 2250 C Nominal size Ø 30 mm	484030 30
Setting ring DIN 2250 C Nominal size Ø 40 mm	484030 40
XT internal micrometer Measuring range 25-35 mm	428500 25-35
Setting ring DIN 2250 C Nominal size Ø 22 mm	484030 22
Extension for internal micrometers Type 4/150	428510 4/150
XT internal micrometer Measuring range 35-50 mm	428500 35-50
XT internal micrometer Measuring range 20-25 mm	428500 20-25
Replacement XT measuring head Measuring range 20-35 mm	428605 20-35
Replacement XT measuring head Measuring range 35-50 mm	428605 35-50