



XT internal micrometer set, Measuring range: 50-100 mm



Order data

Order number	428550 50-100
GTIN	5051102077785
Item class	46B

Description

Version:

3-Point **XT inside micrometers**. Measuring spindle hardened and ground. Micrometer barrel with black scale, all reading parts satin chrome-plated. Ratchet for consistent measuring force. All gauges supplied with serial number and test certificate.

Application:

Blind holes and through holes, centring edges.

Supplied with:

Internal micrometers No. 428500 and setting rings with UKAS test certificate.

Optional extras:

Setting rings No. 484030, extension No. 428510.

Spare part:

Micrometer heads No. 428605.

Calibration: S6

Number of micrometers: 3

Number of setting rings: 2

Setting ring \varnothing : 60 / 80 mm

Technical description

Number of setting rings	2
-------------------------	---

Number of micrometers	3
Measuring range	50 - 100 mm
Setting ring Ø	60 / 80 mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometers

Services

Calibration Internal micrometer set Measuring range 50-100 mm	011240 50-100
Labelling laser-etched Type	018940
Calibration Internal micrometer set Measuring range 50-100 mm	020550 50-100

Accessories

Setting ring DIN 2250 C Nominal size Ø 90 mm	484030 90
XT internal micrometer Measuring range 65-80 mm	428500 65-80
Setting ring DIN 2250 C Nominal size Ø 70 mm	484030 70
Extension for internal micrometers Type 5/150	428510 5/150
Setting ring DIN 2250 C Nominal size Ø 55 mm	484030 55
Replacement XT measuring head Measuring range 80-100 mm	428605 80-100
XT internal micrometer Measuring range 80-100 mm	428500 80-100
Replacement XT measuring head Measuring range 50-65 mm	428605 50-65
Replacement XT measuring head Measuring range 65-80 mm	428605 65-80
XT internal micrometer Measuring range 50-65 mm	428500 50-65

