



Digital XT internal micrometer set, Measurement range: 10-20 mm



Order data

Order number	428652 10-20
GTIN	5051102209681
Item class	46B

Description

Version:

3-point internal micrometer series for blind hole measurement from size 12.5 -16. Fixed carbide measuring jaws, from size 12.5 with carbide inserts. Large, sharp contrast digital display. Measuring spindle through hardened and ground. Reliable measurement without a vernier.

Function:

- **mm / inch selection.**
- **Setting 4 preset values.**
- **On / Off data storage button.**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Digital internal micrometers No. 428602 and setting rings with UKAS test certificate.

Optional extras:

Data cable No. 498948.
 USB dongle No. 498952.
 Setting rings No. 484030.
 Extensions No. 428510.

Spare part:

Spare measuring heads No. 428605, measuring jaws No. 428745, return springs No. 428746.

IP Index of Protection: IP 67

Number of measuring heads: 3

Number of setting rings: 2

Setting ring Ø: 12.5 / 20 mm

Technical description

Number of measuring heads	3
Setting ring Ø	12.5 / 20 mm
Measuring range	10 - 20 mm
Number of setting rings	2
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	DIN 863
Reversible reading	mm / inch
Interface	USB interface
Interface	RS232C interface
Interface	Bluetooth interface
Measurement technology	digital
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometer

Services

Calibration Internal micrometer set Measuring range 10-20 mm	011240 10-20
Labelling laser-etched Type	018940

Accessories

Button cell / special battery Battery type CR2032	081560 CR2032
Digital XT internal micrometer Measurement range 12,5-16 mm	428602 12,5-16

Setting ring DIN 2250 C Nominal size Ø 11 mm	484030 11
Setting ring DIN 2250 C Nominal size Ø 18 mm	484030 18
Bluetooth radio receiver for GARANT and Bowers Type	498952
Extension for internal micrometers Type 2/76	428510 2/76
Connecting cable Type USB2	498948 USB2
Connecting cable Type R2	498948 R2
Digital XT internal micrometer Measurement range 10-12,5 mm	428602 10-12,5
Digital XT internal micrometer Measurement range 16-20 mm	428602 16-20
Extension for internal micrometers Type 3/100	428510 3/100
Setting ring DIN 2250 C Nominal size Ø 14 mm	484030 14
Replacement XT measuring head Måleområde 10-12,5 mm	428605 10-12,5
Replacement XT measuring head Måleområde 12,5-16 mm	428605 12,5-16
Replacement XT measuring head Måleområde 16-20 mm	428605 16-20