



Digital XT internal micrometer set, Measurement range: 100-200 mm



Order data

Order number	428652 100-200
GTIN	5051102209834
Item class	46B

Description

Version:

3-point internal micrometer series for blind hole measurement from size 12.5 -16. Fixed carbide measuring jaws, from size 12.5 with carbide inserts. Large, sharp contrast digital display. Measuring spindle through hardened and ground. Reliable measurement without a vernier.

Function:

- **mm / inch selection.**
- **Setting 4 preset values.**
- **On / Off data storage button.**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Digital internal micrometers No. 428602 and setting rings with UKAS test certificate.

Optional extras:

Data cable No. 498948.
 USB dongle No. 498952.
 Setting rings No. 484030.
 Extensions No. 428510.

Spare part:

Spare measuring heads No. 428605, measuring jaws No. 428745, return springs No. 428746.

IP Index of Protection: IP 67

Number of measuring heads: 4

Number of setting rings: 2

Setting ring Ø: 125 / 175 mm

Technical description

Number of setting rings	2
Measuring range	100 - 200 mm
Setting ring Ø	125 / 175 mm
Number of measuring heads	4
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	DIN 863
Reversible reading	mm / inch
Interface	USB interface
Interface	RS232C interface
Interface	Bluetooth interface
Measurement technology	digital
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometer

Services

Calibration Internal micrometer set Measuring range 100-200 mm	011240 100-200
Labelling laser-etched Type	018940

Accessories

Setting ring DIN 2250 C Nominal size Ø 160 mm	484030 160
Setting ring DIN 2250 C Nominal size Ø 130 mm	484030 130

Connecting cable Type R2	498948 R2
Bluetooth radio receiver for GARANT and Bowers Type	498952
Digital XT internal micrometer Measurement range 125-150 mm	428602 125-150
Setting ring DIN 2250 C Nominal size Ø 190 mm	484030 190
Button cell / special battery Battery type CR2032	081560 CR2032
Digital XT internal micrometer Measurement range 100-125 mm	428602 100-125
Connecting cable Type USB2	498948 USB2
Extension for internal micrometers Type 5/150	428510 5/150
Setting ring DIN 2250 C Nominal size Ø 110 mm	484030 110
Replacement XT measuring head Måleområde 100-125 mm	428605 100-125
Replacement XT measuring head Måleområde 150 mm	428605 150
Replacement XT measuring head Måleområde 150-175 mm	428605 150-175
Replacement XT measuring head Måleområde 175-200 mm	428605 175-200