



Digital XT internal micrometer set, Measurement range: 2-6 mm



Order data

Order number	428652 2-6
GTIN	5051102209629
Item class	46B

Description

Version:

3-point internal micrometer series for blind hole measurement from size 12.5 -16. Fixed carbide measuring jaws, from size 12.5 with carbide inserts. Large, sharp contrast digital display. Measuring spindle through hardened and ground. Reliable measurement without a vernier.

Function:

- **mm / inch selection.**
- **Setting 4 preset values.**
- **On / Off data storage button.**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Digital internal micrometers No. 428602 and setting rings with UKAS test certificate. Two-point gauge

Optional extras:

Data cable No. 498948.
 USB dongle No. 498952.
 Setting rings No. 484030.
 Extensions No. 428510.

Spare part:

Spare measuring heads No. 428605, measuring jaws No. 428745, return springs No. 428746.
 IP Index of Protection: IP 67
 Number of measuring heads: 5

Number of setting rings: 3
 Setting ring Ø: 2.5 / 4 / 5 mm

Technical description

Number of setting rings	3
Number of measuring heads	5
Setting ring Ø	2.5 / 4 / 5 mm
Measuring range	2 - 6 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	DIN 863
Reversible reading	mm / inch
Interface	USB interface
Interface	RS232C interface
Interface	Bluetooth interface
Measurement technology	digital
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal micrometer

Services

Calibration Internal micrometer set Measuring range 2-6 mm	011240 2-6
Labelling laser-etched Type	018940

Accessories

Connecting cable Type USB2	498948 USB2
Button cell / special battery Battery type CR2032	081560 CR2032

Connecting cable Type R2	498948 R2
Bluetooth radio receiver for GARANT and Bowers Type	498952