



Holematic digital XT internal quick measuring device set, Measuring range: 6-10 mm



Order data

Order number	428752 6-10
GTIN	5051102207519
Item class	46B

Description

Version:

3-point internal micrometer series Holematic for blind hole measurement from size 12.5–16. Fixed carbide measuring jaws, from size 12.5–16 with carbide inserts. Large, sharp contrast digital display. Reliable measurement without a vernier.

Advantage:

Very quick and repeatedly accurate measurement due to pistol grip and constant measuring force.

Function:

- **mm / inch selection.**
- **Setting 2 preset values.**
- **On / Off data storage button.**

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Digital internal micrometers No. 428702 and setting rings with UKAS test certificate.

Optional extras:

Data cable No. 498948, USB dongle No. 498952, setting rings No. 484030, extensions No. 428510.

Spare part:

Spare measuring heads No. 428605, measuring jaws No. 428745, return springs No. 428746.

IP Index of Protection: IP 67

Scale divisions: 0.001 mm

Error limit: 0.004 mm

Number of measuring heads: 2
Setting ring Ø: 8 mm

Technical description

Setting ring Ø	8 mm
Scale divisions	0.001 mm
Number of measuring heads	2
Error limit	0.004 mm
Measuring range	6 - 10 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
IP Index of Protection	IP 67
Power supply	Battery-powered
Standard	DIN 863
Reversible reading	mm / inch
Interface	USB interface
Interface	RS232C interface
Interface	Bluetooth interface
Measurement technology	digital
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal quick measuring devices

Services

Labelling laser-etched Type	018940
Calibration Internal micrometer set Measuring range 6-10 mm	011240 6-10

Accessories

Button cell / special battery Battery type CR2032	081560 CR2032
Connecting cable Type R2	498948 R2
Bluetooth radio receiver for GARANT and Bowers Type	498952
Connecting cable Type USB2	498948 USB2
Extension for internal micrometers Type 1/63	428510 1/63
Setting ring DIN 2250 C Nominal size Ø 8 mm	484030 8
Replacement XT measuring head Måleområde 6-8 mm	428605 6-8
Replacement XT measuring head Måleområde 8-10 mm	428605 8-10