



Digital XTL internal quick measuring device, Measuring range: 20-25 mm



Order data

Order number	428760 20-25
GTIN	2050001706454
Item class	46B

Description

Version:

3-point XT internal micrometer series for blind hole measurement from size 12.5–16. Fixed carbide measuring jaws, from size 12.5–16 with carbide inserts. Large, sharp contrast digital display. Reliable measurement without a vernier. Excellently suitable for measuring vertical holes.

Function:

- **mm / inch selection.**
- **Setting 2 preset values.**
- **On / Off data storage button.**

Supplied with:

Measuring lever, micrometer head with UKAS test certificate, 1 battery No. 081560 size CR2032.

Optional extras:

Data cable No. 498950 (from size 20), No. 498951 (up to size 20), setting rings No. 484030, extensions No. 428510.

Calibration: B6

Scale divisions: 0.001 mm

Error limit: 0.004 mm

Dimension a: 0.5 mm

Standard measuring depth: 66 mm

Technical description

Scale divisions	0.001 mm
Standard measuring depth	66 mm
Measuring range	20 - 25 mm

Dimension a	0.5 mm
Measuring depth with extension	216 mm
Error limit	0.004 mm
Article no of the battery / rechargeable battery fitted	081560 CR2032
Number of batteries contained	1
Power supply	Battery-powered
Standard	DIN 863
Reversible reading	mm / inch
Interface	RS232C interface
Interface	USB interface
Measurement technology	digital
Packaging	sturdy box
Calibration	B6
Type of product	3-point quick bore gauge

Services

Labelling laser-etched Type	018940
Calibration 3-point inside micrometer maximum measuring range 50 mm	012900 50
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200
Calibration 3-point inside micrometer maximum measuring range 50 mm	022500 50

Accessories

Setting ring DIN 2250 C Nominal size Ø 22 mm	484030 22
Receiver / USB keyboard interface Type	498965
Setting ring DIN 2250 C Nominal size Ø 24 mm	484030 24

Setting ring DIN 2250 C Nominal size Ø 20 mm	484030 20
Connection cable Duplex Type USB2	498950 USB2
Button cell / special battery Battery type CR2032	081560 CR2032
Transmitter Type S6	498966 S6
Setting ring DIN 2250 C Nominal size Ø 25 mm	484030 25
Extension for internal micrometers Type 4/150	428510 4/150
Connection cable Duplex Type 2	498950 2
Multi-receiver / USB keyboard interface Type	498975