



Digital XTL internal quick measuring set, Measuring range: 6-10 mm



Order data

Order number	428770 6-10
GTIN	5051102120528
Item class	46B

Description

Version:

3-point XT internal micrometer series for blind hole measurement from size 12.5–16. Fixed carbide measuring jaws, from size 12.5–16 with carbide inserts. Large, sharp contrast digital display. Reliable measurement without a vernier. Excellently suitable for measuring vertical holes.

Function:

- **mm / inch selection.**
- **Setting 2 preset values.**
- **On / Off data storage button.**

Supplied with:

Digital internal micrometers No. 428760 and setting rings with UKAS test certificate.

Calibration: S6

Scale divisions: 0.001 mm

Error limit: 0.004 mm

Number of measuring heads: 2

Setting ring \varnothing : 8 mm

Technical description

Number of measuring heads	2
Setting ring Ø	8 mm
Measuring range	6 - 10 mm
Error limit	0.004 mm
Scale divisions	0.001 mm
Number of batteries contained	1
Article no of the battery / rechargeable battery fitted	081560 CR2032
Power supply	Battery-powered
Standard	DIN 863
Reversible reading	mm / inch
Interface	RS232C interface
Interface	USB interface
Measurement technology	digital
Packaging	sturdy box
Calibration	S6
Type of product	3-point internal quick measuring devices

Services

Calibration Internal micrometer set Measuring range 6-10 mm	011240 6-10
Labelling laser-etched Type	018940
Calibration Internal micrometer set Measuring range 6-10 mm	020550 6-10

Accessories

Extension for internal micrometers Type 1/63	428510 1/63
Button cell / special battery Battery type CR2032	081560 CR2032
Setting ring DIN 2250 C Nominal size Ø 7 mm	484030 7
Setting ring DIN 2250 C Nominal size Ø 9 mm	484030 9

Connection cable Duplex Type R2	498951 R2
Connection cable Duplex Type USB2	498951 USB2