



Internal micrometer IMICRO, Measuring range: 8-10 mm



Order data

| | |
|--------------|---------------|
| Order number | 428800 8-10 |
| GTIN | 7630041108057 |
| Item class | 45A |

Description

Version:

Analogue 3-point internal micrometer for **high-precision measurement** of bores, even **at large depths** (can be extended with up to three extensions). Self-centring and self-aligning. Individual internal micrometer to Abbé's principle (**no first order** tilt error). Anvils of hardened steel (HV30–770).

Optional extras:

Setting rings No. 484030, extensions No. 428802.

Note:

Centring devices for large measurement depths on request.

Calibration: B6

Scale divisions: 0.001 mm

Error limit: 0.004 mm

Dimension a: 2.5 mm

Standard measuring depth: 52 mm

Technical description

| | |
|--|-----------|
| Measuring range | 8 - 10 mm |
| Measuring depth with maximum extension | 352 mm |
| Standard measuring depth | 52 mm |
| Dimension a | 2.5 mm |

| | |
|-------------------------------|---------------------------------|
| Error limit | 0.004 mm |
| Scale divisions | 0.001 mm |
| Standard | DIN 863 |
| Micrometer barrel graduations | 1/50 mm |
| Measurement technology | analogue |
| Test certificate | Manufacturer's test certificate |
| Calibration | B6 |
| Type of product | 3-point internal micrometer |

Services

| | |
|--|------------|
| Calibration 3-point inside micrometer maximum measuring range 20 mm | 012900 20 |
| Labelling laser-etched Type | 018940 |
| DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm | 012910 200 |
| DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm | 022510 200 |
| Calibration 3-point inside micrometer maximum measuring range 20 mm | 022500 20 |

Accessories

| | |
|---|--------------|
| Extension for IMICRO internal micrometer Type 1/100 | 428802 1/100 |
| Setting ring DIN 2250 C Nominal size Ø 9 mm | 484030 9 |