



Internal micrometer Micromar, Measuring range: 10-12 mm



Order data

Order number	428900 10-12
GTIN	4059192010591
Item class	43A

Description

Version:

Satin chrome-plated scales and operating parts.

Measuring spindle through-hardened and ground.

Quick drive with integral clutch.

Self-centring micrometer head from 12 mm with carbide measuring jaws.

From 12 mm **for measuring down to the bottom of the hole.**

From 40 mm the micrometer head is of aluminium, to save weight.

Optional extras:

Extension No. 428950, Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.001 mm

Error limit: 0.004 mm

Dimension a: 1.8 mm

Standard measuring depth: 58 mm

Technical description

Dimension a	1.8 mm
Measuring range	10 - 12 mm
Measuring depth with extension	133 mm
Standard measuring depth	58 mm
Error limit	0.004 mm
Scale divisions	0.001 mm
Standard	DIN 863

Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B6
Type of product	3-point internal micrometer

Services

Calibration 3-point inside micrometer maximum measuring range 20 mm	012900 20
Labelling laser-etched Type	018940
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
Calibration 3-point inside micrometer maximum measuring range 20 mm	022500 20
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200

Accessories

Extension for internal micrometer Type 10-20	428950 10-20
Setting ring DIN 2250 C Nominal size \varnothing 11 mm	484030 11