



## Internal micrometer Micromar, Measuring range: 85-100 mm



### Order data

Order number	428900 85-100
GTIN	4059192010393
Item class	43A

### Description

#### Version:

Satin chrome-plated scales and operating parts.

Measuring spindle through-hardened and ground.

Quick drive with integral clutch.

Self-centring micrometer head from 12 mm with carbide measuring jaws.

From 12 mm **for measuring down to the bottom of the hole.**

From 40 mm the micrometer head is of aluminium, to save weight.

#### Optional extras:

Extension No. 428950, Setting rings No. 484030.

Calibration: B6

Scale divisions: 0.005 mm

Error limit: 0.005 mm

Dimension a: 0 mm

Standard measuring depth: 97 mm

### Technical description

Dimension a	0 mm
Standard measuring depth	97 mm
Measuring range	85 - 100 mm
Measuring depth with extension	247 mm
Error limit	0.005 mm
Scale divisions	0.005 mm

Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B6
Type of product	3-point internal micrometer

### Services

Calibration 3-point inside micrometer maximum measuring range 100 mm	012900 100
Labelling laser-etched Type	018940
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	012910 200
DAkkS calibration 3-point internal micrometer maximum measuring range 200 mm	022510 200
Calibration 3-point inside micrometer maximum measuring range 100 mm	022500 100

### Accessories

Extension for internal micrometer Type 25-200	428950 25-200
Setting ring DIN 2250 C Nominal size Ø 90 mm	484030 90